

Declaration of performance according Regulation (EC) no. 305/2011 StyleBoard MDF plus CARB2 - Code 1610
General purpose, non load-bearing boards for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 9 mm to ≤ 11.9 mm
Classification of boards (EN 622-5)	MDF
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 5 ppm
Class of emission, formaldehyde	CARB Phase 2 (Complies with IOS-MAT-0003!)
Internal bond (EN 319)	0.65 N/mm ²
Bending strength (EN 310)	28 N/mm ²
Modulus of elasticity in bending (EN 310)	2500 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 StyleBoard MDF plus CARB2 - Code 1610
General purpose, non load-bearing boards for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	12 mm
Classification of boards (EN 622-5)	MDF
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 5 ppm
Class of emission, formaldehyde	CARB Phase 2 (Complies with IOS-MAT-0003!)
Internal bond (EN 319)	0.60 N/mm ²
Bending strength (EN 310)	28 N/mm ²
Modulus of elasticity in bending (EN 310)	2500 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 StyleBoard MDF plus CARB2 - Code 1610
General purpose, non load-bearing boards for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 12 mm to ≤ 19 mm
Classification of boards (EN 622-5)	MDF
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 5 ppm
Class of emission, formaldehyde	CARB Phase 2 (Complies with IOS-MAT-0003!)
Internal bond (EN 319)	0.60 N/mm ²
Bending strength (EN 310)	27 N/mm ²
Modulus of elasticity in bending (EN 310)	2400 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 StyleBoard MDF plus CARB2 - Code 1610
General purpose, non load-bearing boards for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 19 mm to ≤ 28 mm
Classification of boards (EN 622-5)	MDF
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 5 ppm
Class of emission, formaldehyde	CARB Phase 2 (Complies with IOS-MAT-0003!)
Internal bond (EN 319)	0.55 N/mm ²
Bending strength (EN 310)	25 N/mm ²
Modulus of elasticity in bending (EN 310)	2200 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013