

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard P2 EPF-S - Code 2101
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 9 mm to 13 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 120)	EPF-S
Bending strength (EN 310)	11 N/mm ²
Modulus of elasticity in bending (EN 310)	1800 N/mm ²
Internal bond (EN 319)	0.40 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard P2 EPF-S - Code 2101
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 13 mm to 20 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 120)	EPF-S
Bending strength (EN 310)	11 N/mm ²
Modulus of elasticity in bending (EN 310)	1600 N/mm ²
Internal bond (EN 319)	0.35 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard P2 EPF-S - Code 2101
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 20 mm to 25 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 120)	EPF-S
Bending strength (EN 310)	10.5 N/mm ²
Modulus of elasticity in bending (EN 310)	1500 N/mm ²
Internal bond (EN 319)	0.30 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard P2 EPF-S - Code 2101
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 25 mm to 32 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 120)	EPF-S
Bending strength (EN 310)	9.5 N/mm ²
Modulus of elasticity in bending (EN 310)	1350 N/mm ²
Internal bond (EN 319)	0.25 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard P2 EPF-S - Code 2101
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 32 mm to 40 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 120)	EPF-S
Bending strength (EN 310)	8.5 N/mm ²
Modulus of elasticity in bending (EN 310)	1200 N/mm ²
Internal bond (EN 319)	0.20 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard P2 EPF-S - Code 2101
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 40 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 120)	EPF-S
Bending strength (EN 310)	7 N/mm ²
Modulus of elasticity in bending (EN 310)	1050 N/mm ²
Internal bond (EN 319)	0.20 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013