

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard Fein P2 - Code 2230
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 9 mm to 13 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 13986)	E1
Bending strength (EN 310)	11 N/mm ²
Modulus of elasticity in bending (EN 310)	1800 N/mm ²
Internal bond (EN 319)	0.40 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard Fein P2 - Code 2230

Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal) > 13 mm to 20 mm

Classification of boards (EN 312) P2

Reaction to fire euroclasses (EN 13986) D-s2, d0

Conditions of use (EN 1995-1-1) Service class 1

Content, pentachlorophenol < 3 ppm

Class, formaldehyde release (EN 13986) E1

Bending strength (EN 310) 11 N/mm²

Modulus of elasticity in bending (EN 310) 1600 N/mm²

Internal bond (EN 319) 0.35 N/mm²

Surface soundness (EN 311) 0.8 N/mm²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com

Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard Fein P2 - Code 2230
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 20 mm to 25 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 13986)	E1
Bending strength (EN 310)	10.5 N/mm ²
Modulus of elasticity in bending (EN 310)	1500 N/mm ²
Internal bond (EN 319)	0.30 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard Fein P2 - Code 2230
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 25 mm to 32 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 13986)	E1
Bending strength (EN 310)	9.5 N/mm ²
Modulus of elasticity in bending (EN 310)	1350 N/mm ²
Internal bond (EN 319)	0.25 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard Fein P2 - Code 2230
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 32 mm to 40 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 13986)	E1
Bending strength (EN 310)	8.5 N/mm ²
Modulus of elasticity in bending (EN 310)	1200 N/mm ²
Internal bond (EN 319)	0.20 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

Declaration of performance according Regulation (EC) no. 305/2011 ClassicBoard Fein P2 - Code 2230
Boards for interior fitments (including furniture) for use in dry conditions

Relevant harmonised standard: EN 13986:2004

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

Thickness (nominal)	> 40 mm
Classification of boards (EN 312)	P2
Reaction to fire euroclasses (EN 13986)	D-s2, d0
Conditions of use (EN 1995-1-1)	Service class 1
Content, pentachlorophenol	< 3 ppm
Class, formaldehyde release (EN 13986)	E1
Bending strength (EN 310)	7 N/mm ²
Modulus of elasticity in bending (EN 310)	1050 N/mm ²
Internal bond (EN 319)	0.20 N/mm ²
Surface soundness (EN 311)	0.8 N/mm ²

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • www.pfleiderer.com
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: info@pfleiderer.com



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013