

**Declaration of performance according Regulation (EC) no. 305/2011    StyleBoard MDF tiefräs+ CARB2 - Code 1620**  
**General purpose, non load-bearing boards for use in dry conditions**

Relevant harmonised standard: EN 13986:2004

---

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

---

<b>Thickness (nominal)</b>	16 mm
<b>Classification of boards (EN 622-5)</b>	MDF
<b>Reaction to fire euroclasses (EN 13986)</b>	D-s2, d0
<b>Conditions of use (EN 1995-1-1)</b>	Service class 1
<b>Content, pentachlorophenol</b>	< 5 ppm
<b>Class of emission, formaldehyde</b>	CARB Phase 2 (Complies with IOS-MAT-0003!)
<b>Internal bond (EN 319)</b>	0.70 N/mm <sup>2</sup>
<b>Bending strength (EN 310)</b>	30 N/mm <sup>2</sup>
<b>Modulus of elasticity in bending (EN 310)</b>	2500 N/mm <sup>2</sup>

---

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • [www.pfleiderer.com](http://www.pfleiderer.com)  
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: [info@pfleiderer.com](mailto:info@pfleiderer.com)



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

**Declaration of performance according Regulation (EC) no. 305/2011    StyleBoard MDF tiefräs+ CARB2 - Code 1620**  
**General purpose, non load-bearing boards for use in dry conditions**

Relevant harmonised standard: EN 13986:2004

---

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

---

<b>Thickness (nominal)</b>	> 17.9 mm to ≤ 19 mm
<b>Classification of boards (EN 622-5)</b>	MDF
<b>Reaction to fire euroclasses (EN 13986)</b>	D-s2, d0
<b>Conditions of use (EN 1995-1-1)</b>	Service class 1
<b>Content, pentachlorophenol</b>	< 5 ppm
<b>Class of emission, formaldehyde</b>	CARB Phase 2 (Complies with IOS-MAT-0003!)
<b>Internal bond (EN 319)</b>	0.70 N/mm <sup>2</sup>
<b>Bending strength (EN 310)</b>	30 N/mm <sup>2</sup>
<b>Modulus of elasticity in bending (EN 310)</b>	2500 N/mm <sup>2</sup>

---

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • [www.pfleiderer.com](http://www.pfleiderer.com)  
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: [info@pfleiderer.com](mailto:info@pfleiderer.com)



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013

**Declaration of performance according Regulation (EC) no. 305/2011    StyleBoard MDF tiefräs+ CARB2 - Code 1620**  
**General purpose, non load-bearing boards for use in dry conditions**

Relevant harmonised standard: EN 13986:2004

---

The manufacturer assesses and controls the consistency of performance of the mentioned product according system 4, European Standard 13986. He has installed a factory production control according European Standard 13986.

---

<b>Thickness (nominal)</b>	22 mm
<b>Classification of boards (EN 622-5)</b>	MDF
<b>Reaction to fire euroclasses (EN 13986)</b>	D-s2, d0
<b>Conditions of use (EN 1995-1-1)</b>	Service class 1
<b>Content, pentachlorophenol</b>	< 5 ppm
<b>Class of emission, formaldehyde</b>	CARB Phase 2 (Complies with IOS-MAT-0003!)
<b>Internal bond (EN 319)</b>	0.70 N/mm <sup>2</sup>
<b>Bending strength (EN 310)</b>	28 N/mm <sup>2</sup>
<b>Modulus of elasticity in bending (EN 310)</b>	2200 N/mm <sup>2</sup>

---

Pfleiderer Holzwerkstoffe GmbH • Ingolstädter Str. 51 • 92318 Neumarkt • [www.pfleiderer.com](http://www.pfleiderer.com)  
Phone: ++49 (0) 9181 - 28 480 • Fax: ++49 (0) 9181 - 28 482 • Mail: [info@pfleiderer.com](mailto:info@pfleiderer.com)



i. V. Claus Seemann (Leitung Produktmanagement Träger)

25.07.2013