

DECLARATION OF PERFORMANCE – Ref.-No.051-CPR

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	High-pressure decorative compact laminate type CGS-AR High-pressure decorative compact laminate with design effect type ACS-AR				
2. Identification	Code CGS-AR - Duropal-HPL Compact, black core Code ACS-AR- Duropal-HPL Compact Metallic, black core				
3. Intended use	Compact laminate intended for internal wall and ceiling finishes (including suspended ceilings)				
4. Manufacturer	Pfleiderer Arnsberg GmbH, Westring 19-21, D-59759 Arnsberg				
5. Authorised representative	Pfleiderer Holzwerkstoffe GmbH, Ingolstädter Straße 51, D-92318 Neumarkt				
6. System of assessment and verification	System 4				
7. European Technical Assessment	Not relevant				
8.	Not relevant				
9. Declared performance					
	Product-type	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR	CGS-AR ACS-AR
	Thickness	3 mm	6 mm	8 mm	10 – 15 mm
<i>Essential characteristics</i>	<i>Performance</i>				<i>Harmonised technical specification</i>
Reaction to fire	Euroclass ≤ 5 mm: NPD	Euroclass > 5 mm: D-s2,d0	Euroclass > 5 mm: D-s2,d0	Euroclass > 5 mm: D-s2,d0	EN 438-7:2005
Fire resistance	NPD				
Water vapour permeability	wet cup: 110 / dry cup: 250				
Resistance to fixings	≥ 250 N	≥ 2.000 N	≥ 3.000 N	≥ 4.000 N	
Direct airborne sound insulation	NPD				
Flexural tensile strength	Passed				
Thermal resistance	NPD				
Release to formaldehyde	E1				
Sound absorption	NPD				
Durability	Resistance to boiling water: Passed				
Density	≥ 1.350 kg/m ³				
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.					

Signed for and on behalf of the manufacturer by:



Arnsberg, 2013-08-26

Markus Frevert
General Manager / Pfleiderer Arnsberg GmbH

NPD: No Performance Determined